



**PHYSICAL CONSTRUCTION:**

CONSTRUCTION: Tufted Patterned Loop (Non-Phthalate Construction)

FACE FIBER: 100% Econyl® Regenerated Type 6 Nylon  
DYE METHOD: Solution  
GAUGE: 5/64  
STITCHES PER INCH: 9.16  
TUFTED PILE HEIGHT: .156 Inches (avg)  
TUFTED YARN WEIGHT: 14 Ounces Per Square Yard  
PRIMARY BACKING: 100% Synthetic  
SECONDARY BACKING: Infinity Modular Reinforced Composite Closed Cell Polymer  
STANDARD SIZE: 24" X 24" Modular Tiles

**ENVIRONMENTAL:**

RECYCLED CONTENT: Contains Pre-Consumer Recycled Content  
MANUFACTURE LOCATION: Calhoun, Georgia 30701 USA  
NSF / ANSI-140 CERTIFICATION: Gold  
CRI GREEN LABEL PLUS ID: GLP7616

**WARRANTIES:**

WARRANTY: Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection  
BLEACH RESISTANT WARRANTY: ColorSafe® with 15 Year Limited Warranty Against Color Loss from Bleach Spills  
STAIN RESISTANT WARRANTY: XGUARD® with 15 Year Limited Warranty Against Staining

**PRODUCT TESTING:**

RADIANT PANEL (ASTM E-648): Class I (Direct Glue)  
SMOKE CHAMBER (ASTM E-662): Less than 450 (Flaming Mode)  
METHENAMINE PILL TEST (ASTM D-2859): Passes  
DIMENSIONAL STABILTY AACHEN TEST: Passes  
ELECTROSTATIC PROPENSITY (AATCC 134): Less than 3.5 KV

**RECOMMENDED ADHESIVE:**

RELEASEABLE ADHESIVE: Mannington Infinity Pressure Sensitive Adhesive  
CRI GREEN LABEL PLUS ID: GLP70522  
VOC LIMITS: Meets SCAQMD Rule #1168  
BOND WARRANTY: Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.



updated 10/31/17