



DAKOTA SPC CLICK



Waterproof Rigid Core

Property/Standard	<i>*Stocking Salesmaster product w/ Domestic Backup Stock in the USA*</i>	Value/Result
Overall Thickness		5mm (4mm + 1mm pad)
Wearlayer Thickness		20mil
Backing		High Density EVA Pad
Finish		Aluminum Oxide
Plank Size		7" x 60"
Square Edge		No
Commercial Warranty		15 Year Commercial
Residential Warranty		Lifetime
Installation Method		Click
Floor Score		Yes
Sound Transmission Class Impact Insulation Class	6" Slab with Suspended Ceiling 6" Slab without Suspended Ceiling	STC: 63 IIC: 65 STC: 57 IIC: 59
Packaging		29.89 SF/Ctn
Package Weight		51 Lbs./Ctn

Test Data:

- ASTM-E648 Critical Radiant Flux: Meets or exceeds, Class 1
- ASTM-C1028-07 Static Coefficient of Friction: 0.79 (slip resistance) - Passes ADA/OSHA standard
- ASTM-F2055-17 Length, Width & Squareness: Pass
- ASTM-D3884-09 Rotate Abrasion Resistance: Pass
- ASTM-F1515 Color Resistance to Light: Meets Requirement
- ASTM-F925-13 Resistance to Chemicals: Pass (No Change)
- ASTM-F1514-18 Residual Indentation: Pass (0-01%)
- ASTM-F1914 Color Resistance to Heat: Meets Requirements
- ASTM-F2199-09 Dimensional Stability After Heat Exposure: Pass (Less than .01%)
- ASTM-F963-17 Lead & Soluble Heavy Metal: None Detected
- ASTM-E90-09 Airborne Sound Conduction: STC 63 db (with ceiling)
- ASTM-E90-09 Airborne Sound Conduction: STC 57 db (without ceiling)
- ASTM-E492-09 Impact Sound Conduction: IIC 65 db (with ceiling)
- ASTM-E492-09 Impact Sound Conduction: IIC 59 db (without ceiling)
- ASTM-E2179 Impact Sound Transmission Δ 22 IIC