

# TeMPO

## TECH DATA + TEST SPECIFICATIONS

2mm 12mil Glue Down

Property/Standard	Description	Value / Result
<b>Overall Thickness</b>		2.0 mm
<b>Wearlayer Thickness</b>		12mil / 0.3 in.
<b>Tile Size</b>	ASTM F 2055	7" x 48"
<b>Bevelled Edge</b>		No
<b>Classification</b>	EN ISO 10582 ASTM F 1700	22+: Domestic General Class II Type A
<b>Reaction to Fire</b>	EN13501-1 EN ISO 11925-2 EN ISO 9239-1	B <sub>n</sub> – S1 Pass Pass
<b>Resistance to Chemicals</b>	EN 423 ASTM F 925	Class 0 Pass
<b>Resistance to Light</b>	EN ISO 105-B02 ASTM F 1515	≥6 <8
<b>Wear Resistance</b>	EN 660-2 ASTM F 510	Wear Group: T
<b>Dimensional Stability</b>	EN 434 ASTM F 2199	≤0.25 % Pass
<b>Acoustic Impact Noise Reduction</b>	EN ISO 717-2 EN ISO 140-8	ΔL <sub>w</sub> = 4 dB
<b>Static Electrical Propensity</b>	EN 1815	Voltage: 0.5kV
<b>Residual Indentation</b>	EN 433 ASTM F 1914	≤0.1 mm < 8 %
<b>Anti-Slip Property</b>	DIN 51130	R10
<b>VOC Emission</b>	ISO 16000	A+
<b>Phthalates</b>	EN 14372 CPSC-CH-C 1001-09.3	N.D Pass
<b>Castor Chair Continuous Use</b>	ISO 4918	Pass
<b>Squareness</b>	ASTM F 2055	Pass